

Silicon Diode

FE6C

Fast Efficient Rectifier

150V / 6A

DATASHEET

from

www.web-bcs.com

OEM – General Semiconductor

Source: General Semiconductor Databook 1998

FE6A THRU FE6D


GLASS PASSIVATED FAST EFFICIENT RECTIFIER

Reverse Voltage - 50 to 200 Volts

Forward Current - 6.0 Amperes

PATENTED*

Case Style G4



Dimensions in inches and (millimeters)

* Brazed lead assembly is covered by Patent No. 3,930,306

FEATURES

- ◆ High temperature metallurgically bonded construction
- ◆ Glass passivated cavity-free junction
- ◆ Superfast recovery time-for high efficiency
- ◆ Low forward voltage, high current capability
- ◆ Capable of meeting environmental standards of MIL-S-19500
- ◆ Hermetically sealed package
- ◆ Low leakage current
- ◆ High surge current capability
- ◆ High temperature soldering guaranteed: 350°C/10 seconds, 0.375" (9.5mm) lead length, 5 lbs, (2.3kg) tension



MECHANICAL DATA

Case: Solid glass body

Terminals: Plated axial leads, solderable per MIL-STD-750, Method 2026

Polarity: Color band denotes cathode end

Mounting Position: Any

Weight: 0.037 ounce, 1.04 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

	SYMBOLS	FE6A	FE6B	FE6C	FE6D	UNITS
Maximum repetitive peak reverse voltage	V _{RRM}	50	100	150	200	Volts
Maximum RMS voltage	V _{RMS}	35	70	105	140	Volts
Maximum DC blocking voltage	V _{DC}	50	100	150	200	Volts
Maximum average forward rectified current 0.375" (9.5mm) lead length at T _L =55°C	I _(AV)	6.0				Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}	135.0				Amps
Maximum instantaneous forward voltage at 6.0A	V _F	0.975				Volts
Maximum DC reverse current at rated DC blocking voltage	I _R	5.0 50.0				μA
Maximum reverse recovery time (NOTE 1)	t _{rr}	35.0				ns
Typical junction capacitance (NOTE 2)	C _J	100.0				pF
Typical thermal resistance (NOTE 3, 4)	R _{θJA} R _{θJL}	55.0 18.0				°C/W
Operating junction and storage temperature range	T _J , T _{STG}	-65 to +175				°C

NOTES:

- (1) Reverse recovery test conditions: I_F=0.5A, I_R=1.0A, I_{SM}=0.25A
- (2) Measured at 1.0 MHz and applied reverse voltage of 4.0 Volts
- (3) Thermal resistance from junction to lead at 0.375" (9.5mm) lead length with both leads attached to heatsinks
- (4) Thermal resistance from junction to ambient at 0.375" (9.5mm) lead length and mounted on P.C.B.

RATINGS AND CHARACTERISTIC CURVES FE6A THRU FE6D

FIG. 1 - MAXIMUM FORWARD CURRENT DERATING CURVE




FIG. 2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4 - TYPICAL REVERSE LEAKAGE CHARACTERISTICS




FIG. 5 - TYPICAL JUNCTION CAPACITANCE

